



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|--------------------|------------------------|--|
| FINISH: | Polished Chrome | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Metal - Mild Steel | GROSS WEIGHT: | 2.47 (kg) |
| DIMENSIONS: | H: 80mm DIA: 300mm | CLASS: | CE (Class II) |
| INSTALLATION ORIENTATION: | Ceiling Mount | IP RATING: | IP44 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 2, 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230V |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Not suitable for mounting on flammable materials |


LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | LED Module | MACADAM ELLIPSE: | 6 MacAdam |
| MAXIMUM WATTAGE: | 16W | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | Not Applicable |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | 673 (lm) | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 2700 (K) | AVERAGE LIFESPAN: | 20,000 (Hrs) |
| CRI: | >80 | L70: | To Be Advised |
| R9: | 10 | | |

ELECTRICAL

| | | | |
|-------------------------------|----------------|-----------------------------------|-------------------------|
| SWITCHED: | Not Applicable | SUPPLY FREQUENCY: | 50/60 (Hz) |
| DIMMABLE: | No | DRIVER / BALLAST VOLTAGE: | 220-240 (V) |
| DIMMING METHOD: | Not Applicable | DRIVER AVERAGE LIFESPAN: | 20,000 (Hrs) switch cry |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | 43 (lm/W) |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | Yes (Integral) |

ADDITIONAL INFORMATION



BOX QUANTITY X4

PRODUCT ELEVATIONS

