



PRODUCT SPECIFICATION

GENERAL

FINISH:	Matt White	CABLE LENGTH:	1000 (mm)
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	1.026 (Kg)
DIMENSIONS:	H:177mm DIA:146mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Install in to new ceiling	IP RATING:	IP65
CUT OUT HOLE:	95mm/3-3/4"	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	177 (mm)	VOLTAGE:	Constant Current 250 (mA)
FIRE RATING:	90 min	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP


LIGHT SOURCE:	COB LED	MACADAM ELLIPSE:	3-Step
MAXIMUM WATTAGE:	9.1W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	25 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	877.36 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	To Be Advised
CRI:	80	L70:	To Be Advised
R9:	11.5		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER/BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Control Gear Dependant	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	82.77 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	Not applicable

ADDITIONAL INFORMATION

Product tested with 1836 - LED Driver CC 250/350/500/700mA DALI Dim



BOX QUANTITY x 8



PRODUCT ELEVATIONS



95mm / 3-4/4"

